Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Airam

Supplier's address: Airam Electric Oy Ab, Sementtitehtaankatu 6, FI-04260 Kerava, FI

Model identifier: 4713894

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No


Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	G
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)		350 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1800...3000
On-mode power (P_{on}), expressed in W		4,9	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,35
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81...89
Outer dimensions without separate control gear, lighting control	Height	172	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width	125		
	Depth	125		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[(a)]		Yes	If yes, equivalent power (W)	34
			Chromaticity coordinates (x and y)	0,440 0,403
Parameters for LED and OLED light sources:				
R9 colour rendering index value		1	Survival factor	0,90
the lumen maintenance factor		0,90		
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ1)		0,50	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		-[(b)]	If yes then replacement claim (W)	-
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,9

[(a)] '-' : not applicable;

[(b)] '-' : not applicable;


Spectrum
1.0=11.521mW/nm
1.2
1.0
0.8
0.6
0.4
0.2
0.0
350
513
675
838
1000
Wavelength (nm)

Model placed on the Union market from 26/03/2021

EPREL registration number: 552642

https://eprel.ec.europa.eu/qr/552642

Supplier: Airam Electric Oy Ab (Manufacturer)

Website:

Customer care service:

Name: Airam Electric Oy Ab

Website: www.airam.fi

Email: asiakaspalvelu@airam.fi

Phone: +358 207 545 600

Address:
Sementtitehtaankatu 6
FI-04260 Kerava
Finland