# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Airam

**Supplier's address:** Airam Electric Oy Ab, Sementtitehtaankatu 6, FI-04260 Kerava, FI

**Model identifier:** 4713876

**Type of light source:**

| | | | |
|---|---|---|---|
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | E14 | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | Yes |
| Colour-tuneable light source: | Yes | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |


**Product parameters**

| Parameter | Value | Parameter | Value |
|---|---|---|---|
| **General product parameters:** | | | |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer | 5 | Energy efficiency class | F |
| Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º) | 470 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2700...6500 |
| On-mode power ($P_{on}$), expressed in W | 4,9 | Standby power ($P_{sb}$), expressed in W and rounded to the second decimal | 0,35 |
| Networked standby power ($P_{net}$) for CLS, expressed in W and rounded to the second decimal | 0,50 | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 81...89 |
| Outer dimensions without separate control gear, lighting control — Height | 106 | Spectral power distribution in the range 250 nm to 800 nm, at full-load | See image in last page |
| Outer dimensions without separate control gear, lighting control — Width | 37 | | |
| Outer dimensions without separate control gear, lighting control — Depth | 37 | | |

| | | | | |
|---|---|---|---|---|
| parts and non-lighting control parts, if any (millimetre) | | | | |
| Claim of equivalent power[(a)] | | Yes | If yes, equivalent power (W) | 40 |
| | | | Chromaticity coordinates (x and y) | 0,313<br>0,337 |
| **Parameters for LED and OLED light sources:** | | | | |
| R9 colour rendering index value | | 1 | Survival factor | 0,90 |
| the lumen maintenance factor | | 0,90 | | |
| **Parameters for LED and OLED mains light sources:** | | | | |
| displacement factor (cos ϕ1) | | 0,50 | Colour consistency in McAdam ellipses | 6 |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | | -[(b)] | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | | 1,0 | Stroboscopic effect metric (SVM) | 0,9 |

[(a)] '-' : not applicable;

[(b)] '-' : not applicable;


Spectrum
1.0=29.999mW/nm
1.2
1.0
0.8
0.6
0.4
0.2
0.0
350
513
675
838
1000
Wavelength(nm)

Model placed on the Union market from 26/03/2021

**EPREL registration number:** 552641

https://eprel.ec.europa.eu/qr/552641

**Supplier:** Airam Electric Oy Ab (Manufacturer)

**Website:**

**Customer care service:**

**Name:** Airam Electric Oy Ab

**Website:** www.airam.fi

**Email:** asiakaspalvelu@airam.fi

**Phone:** +358 207 545 617

**Address:**
Sementtitehtaankatu 6
FI-04260 Kerava
Finland